MDVR4
4CH 1HDD MDVR

Main Features

4CH

Connect up to 4 channels

2 MP

Up to 2 x 2MP Analog cameras

HDMI

HDMI Video Output

With WIFI option

Support up to 2TB HDD

Operating Temperature -25°C to 55°C

Power output for cameras

4G

With 4G option

Video	
Video Input	Maximum for 2x 1080p or 4x 720p/540p Analog/AHD cameras
Video Output	1 x HDMI, 1 x CVBS
Frame Rate	30fps@1080P 2x Analog/AHD cameras or 30fps@720p for 4x Analog/AHD cameras
Display Split	1/2/4
Video Compression	H.264
Record Mode	Auto Record, Schedule Record, Alarm Record
Record Resolution	Support 1920x1080/ 1280x720/ 960x540
Record Frame Rate	Recording frame rate: 1 ~ 30fps selectable for each camera
Audio	
Audio Input	4 audio input (camera with built-in audio)
Audio Compression	AAC (16bit, 48KHz) and PCM (according to different camera models)
Network	
Bitrate	100 ~ 8000 kbps for each camera
Frame Rate	30fps@1080P 2x Analog/AHD cameras or 30fps@720p for 4x Analog/AHD cameras
Protocol	TCP/IP
4G (Optional)	Build in 4G (HSUPA/HSDPA/WCDMA/EVDO/TDSCDMA/FDD-LTE/TDD-LTE)
WIFI (Optional)	Support WIFI
Firmware Upgrade	Can use hard disk/USB disk/SD card/remote upgrade via 4G
Alarm	
Alarm Input	3 x alarm sensors input, 1 x speed input, 1 x ignition input, 1 x panic button alarm
Alarm Output	1 x alarm output
Event	Video Loss Event, Storage Event, Motion Detection Event, Panic Button Event
Storage	
Hard Disk	Up to 2TB
SD Card	Up to 256GB
ACC	
<4.5V	Ignition Off
>6.2V	Ignition On
External Interface	
RS485	Y
RS232	Y
RJ45	Y
USB	Y
General	
Operating Temperature	-25^{0}C ~ 55^{0}C
Relative Humidity	5% ~ 93%
Operating Voltage	8 ~ 32VDC
Output Voltage	Power output for cameras – 10.5V/1.5A (8 cameras)
Power Consumption	<5W (without camera)
Dimensions	162.3 x 133 x 30.2 mm
Weight	Approximate 0.55KG

Ventionex

MDVR4 – X

WIFI 4G Options
W   : With WIFI
G   : With 4G
WG   : With WIFI & 4G

Standard Accessories

TC-MDVR   : Tamper-Proof Case